



耐火間仕切壁(小屋裏まで):石膏板・ト(7)12.5mm2枚張り
(耐火間仕切壁貫通部は、令114条区画貫通処理を行う。)

2階平面図 S=1/100

※直通階段への歩行距離(重複距離)の検討

a-x間	4.500+9.140+6.560+7.820+0.520=28.540m
a-y間	4.500+9.140+4.950+9.420+1.940=29.950m
重複距離	4.500+9.140=13.640m
b-x間	4.930+6.760+1.680+6.560+4.950+7.820+0.520=33.220m
b-y間	4.930+6.760+1.680+9.420+1.940=24.730m
重複距離	4.930+6.760+1.680=13.370m
c-x間	4.430+7.520+3.350+1.680+6.560+4.950+7.820+0.520=36.830m
c-y間	4.430+7.520+3.350+1.680+9.420+1.940=28.340m
重複距離	4.430+7.520+3.350+1.680=16.980m
d-x間	4.990+4.070+0.870=9.930m
d-y間	4.990+4.070+5.230+2.740+2.100+4.760+9.540+4.310+2.330=40.070m
重複距離	4.990+4.070=9.060m
e-x間	6.520+7.670+5.230+0.870=20.290m
e-y間	6.520+7.670+2.740+2.100+4.760+9.540+4.310+2.330=39.970m
重複距離	6.520+7.670=14.190m
f-x間	4.200+3.580+5.230+0.870=13.880m
f-y間	4.200+3.580+2.740+2.100+4.760+9.540+4.310+2.330=33.560m
重複距離	4.200+3.580=7.780m
g-x間	2.200+2.470+2.740+5.230+0.870=13.510m
g-y間	2.200+2.470+2.100+4.760+9.540+4.310+2.330=27.710m
重複距離	2.200+2.470=4.670m
h-x間	1.720+2.220+2.100+2.740+5.230+0.870=14.880m
h-y間	1.720+2.220+4.760+9.540+4.310+2.330=24.880m
重複距離	1.720+2.220=3.940m